

Chiller with air-cooled refrigerating unit and circulation pump. Evaporator (cooler), tank and housing of stainless steel. Pressure-suction pump made of industrial plastic material. Digital Temperature adjustment and digital temperature display. Level indicator with sight glass.

OLÉ controller:

The controller combines state-of-the-art technology with simple operation. Models with OLÉ controller are suitable for routine tasks in research and industry and are convincing as practice oriented basic equipment:

- \* Large, bright OLED display
- \* Simple operation with menu navigation
- \* Simultaneous display of set point, internal temperature, Tmin and Tmax
- \* USB (Device) and RS232 interfaces
- \* Autostart function for power failure

Option: Pt100 sensor connection #10519 to display (not control) e.g. of the process temperature (only available factory fitted, additional charge)

4-year warranty - registration required.

## Technical data according to DIN 12876

Operating temperature range	-5...40 (80)*** °C
temperature set point / display	digital
Internal temperature sensor	NTC
Resolution of display	0,1 K
Interface digital	USB (Device), RS232
Alarm message	Interface
Temperature stability at 0°C	optic, acoustic
Safety classification	1 K
Cooling power	I / NFL
at 15°C	0,28 kW
at 0°C	0,2 kW
Refrigeration machine	air-cooled, natural
Refrigerant (ASHRAE, GHS)	refrigerant
Global Warming Potential (GWP)	R-290 (A3, H220)
Refrigerant quantity	0,02
CO2 equivalent	0,041 kg
Circulation pump	0,0 t
	Pressure- and suction
max. delivery	pump
max. delivery pressure	14 l/min
max. delivery (suction)	0,25 bar
max. delivery pressure (suction)	10,5 l/min
Pump connection	0,17 bar
min. filling capacity	M16x1 male
expansion tank	1,4 l
Overall dimensions WxDxH **	2 l
Net weight	225x360x380 mm
sound pressure level +/- 4 dB(A)	23 kg
Power supply requirement	49 dB(A)
max. current	110-120V 1~ 60Hz
min. Fuse	4 A
max. Fuse	10A
Pressure equipment category	16A
Degree of Protection	Art. 4.3 PED
min. ambient temperature	IP20
max. ambient temperature	5 °C
	40 °C



**Order-No.: 3065.0002.98**

**from Serial-No.: S395905**

**1.0/20**

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

## Technical data according to DIN 12876

---

### Included Accessories:

hose connector NW12 #6087, sleeve nuts thread M16x1#6089, blank plug, cover expansion vessel #25178,

### Optional accessories:

Drain valve #6839, temperature control / -connection hoses, heat transfer fluid, further accessories, etc.: see catalog.

Output data valid for: Room temperature 20°C. If the ambient temperature rises, the cooling capacity may drop.

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

### Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer).

It is recommended that water is mixed with either glysantine or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

### Standard delivery conditions - Power cable configuration:

1. Single / two-phase devices (100V to 240V) --> with power cable and country-specific plug (please specify when ordering)
2. Three-phase devices with current consumption less than 63A --> with cable, without plug
3. Three-phase devices with current consumption greater than 63A --> without cable, without plug

This equipment is compliant to US-SNAP and all applicable EU laws. The US-SNAP end-use for this equipment is the industrial process refrigeration. Certification by a Notified Body upon request.

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)

\*\*\* Permissible temperature in return line 80 °C